

150mic Clear Cling Gloss (S301)

A clear static cling PVC with a glossy finish. Ideal for all window displays. The static cling adhesion allows for removal without residue. Easy to remove and re-use.

TECHNICAL SPECIFICATION

| | Value | T Method |
|-----------|--------|----------|
| Thickness | 150mic | |
| Backing | 130gsm | |

AVAILABLE SIZES

| | | | |
|--------|-------|-------|---------|
| 1372mm | (54") | x 25m | 3" Core |
|--------|-------|-------|---------|

APPLICATIONS AND CHARACTERISTICS

- Suitable for high quality durable signage
- Suitable for indoor use for up to 3 years (1 year outdoors)
- For use with eco, eco+, eco ultra and solvent inks
- Accepts high ink coverage
- Excellent sharp colourful images
- Short drying times

PRINTER COMPATIBILITY CHART

Printer and driver settings may need careful calibration to ensure optimum performance. Ink loads need to be calibrated for the combination of the printer and ink being used.

| MANUFACTURER | MODEL | INKS |
|--------------|-------|------|
|--------------|-------|------|

All of our products undergo thorough testing on all leading printers and with all major manufactured inks. But to guarantee that you get the best possible results every time from our products and printers inks, it is advisable to consult your representative.

APPLICATION NOTES

The minimum application temperature is +5°C. The service temperature range is -10°C to +50°C.

STORAGE AND TRANSPORT

The ideal storage conditions for this product are 33-65% relative humidity with temperatures of +10°C to +25°C. We recommend that you always keep this product in its original packaging.