PRODUCTDATA

Digital

Last change: February 8, 2019



be.tex® Floor 900 FR | Product no.: 5010-6







PRODUCT FEATURES

Material: 100% polyester Weight: 900 g/m² Thickness: 2800 µm Transmission factor: 0 %

WIDTH LENGTH (cm) (m)

ca. 160 ca. 25 ca. 400 ca. 25 *

* Attention: 4 inch core

APPLICATIONS

sound / noise absorbing home / interior / decoration

FEATURES

water tight good flatness sound absorbing

DESCRIPTION

The market standard from Captiqs® as printable version exclusive from A. Berger for exhibition, customized carpets, POS etc.. Like defined in standard EN 14041 be.tex® Floor 900 FR fulfilled according to EN 13893 a dynamic coefficient of friction μ of \geq 0,3 and shall be declared as technical class DS ("Dry Slip resistant"). Comes on 4 inch/100mm tubes.

NOTES

Fire resist: DIN EN 13501-1 (Cfl-S1) Sound absorption: aW = 0,10 (H) Impact sound insulation: $\Delta LW = 18dB$ Attention: 25m roll length = 31cm diameter

The numbers above are purely guidelines and may differ depending on your personal printing needs and expectations. Since the printing results depend on numerous factors, we strongly advise to test your output in order to find out if any adjustments are necessary. A legally binding assurance of certain properties of the fabric can not be derived from the information above.